PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7: WO 00/53382 (11) International Publication Number: **B29B A2** (43) International Publication Date: 14 September 2000 (14.09.00) PCT/US00/05991 (21) International Application Number: (81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, (22) International Filing Date: 8 March 2000 (08.03.00) IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, CY, DE, DK, ES, FI, (30) Priority Data: 8 March 1999 (08.03.99) US FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). 60/123,257 (71)(72) Applicants and Inventors: WARD, Vincent, C. [US/US]; Published Without international search report and to be republished 6504 Mayfair, Houston, TX 77087 (US). WARD, Mark, V. [ZA/US]; 6504 Mayfair, Houston, TX 77087 (US). WARD, upon receipt of that report. Bryce, D. [US/US]; 6504 Mayfair, Houston, TX 77087 (US). (74) Agent: CURINGTON, Tim, W.; 1700 W. Loop South, Suite 1700, Houston, TX 77027 (US).

(54) Title: WATER JET ABRASIVE RECYCLING APPARATUS AND METHOD

(57) Abstract

A preferred embodiment of the present invention relates to an abrasive recovery apparatus for use in confinction with the slurry generated by water jet cutting or conditioning operations. The generated slurry is comprised of both non-recyclable fines and recyclable particles. The abrasive recovery apparatus comprises a slurry intake system having one or more pumps which collect and distribute slurry. The abrasive recovery apparatus further comprises a vibrating separator having a filter sized and shaped such that the non-recyclable fines in the slurry are separated from the recyclable particles in the slurry. The abrasive recovery apparatus still further comprises a fluidized bed dryer having heating elements to dry the recyclable particles.

